



* H = HEIGHT OF CURB
ALL MEASUREMENTS IN INCHES

PLAN



ELEVATION



SECTION A-A

NOTES

1. TO BE USED WHERE A PEDESTRIAN ACCESS ROUTE CROSSES RAISED MEDIANS OR RAISED ISLANDS AND THERE IS SUFFICIENT WIDTH TO SATISFY THE GEOMETRY OUTLINED IN THIS STANDARD.
2. EXPANSION JOINT MATERIAL SHALL BE INSTALLED IN ACCORDANCE WITH STANDARD BC 655.01.
3. RAMPED MEDIAN AND ISLAND OPENINGS TO BE SHOWN ON PLANS SYMBOLICALLY AND REFERENCED WITH THE CENTER OF THE OPENING ALIGNED TO A STATION ON THE CONSTRUCTION CENTERLINE. SEPARATE DETAILS SHALL BE SHOWN WHERE PROPOSED OPENING VARIES FROM STANDARD METHODS.
4. WHERE 60" OPENINGS CANNOT BE USED A DESIGN WAIVER MUST BE REQUESTED.



APPROVED:

Bimal Dora
DIVISION CHIEF, TRANSPORTATION ENGINEERING
AND CONSTRUCTION
Husein Raza
DIRECTOR, DEPARTMENT OF TRANSPORTATION

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION
ENGINEERING AND
CONSTRUCTION

RAMPED
MEDIAN AND ISLAND OPENINGS

ISSUED	REVISED	REVISED
8 / 2010	10 / 2013	08/2024

STANDARD NO.
BC 655.22

SCALE : NONE

SHEET 1 OF 1