



NOTES:

1. WHEN "W" IS 6" OR LESS, SPACE POSTS 8'-0" C.C.
2. WHEN "W" IS GREATER THAN 6", SPACE POSTS 6'-0" C.C.
3. WHEN "D" IS LESS THAN 36", MEASURE 27" MOUNTING HEIGHT "H" FROM PAVT TO TOP OF RAIL.
4. WHEN "D" IS 36" OR GREATER MEASURE 27" MOUNTING HEIGHT "T" FROM BACK OF CURB TO TOP OF RAIL.
5. FOR DETAILS NOT SHOWN ON THIS SHEET SEE BC 662.51-2 & BC-662.61-1.

DETAIL OF ALTERNATE POST ANCHOR FOR PAVED MEDIANS

DETAIL SECTION FOR RAISED MEDIAN



APPROVED:
Frank Murphy
 DEPUTY DIRECTOR - OPERATIONS
Khalil Zane
 DIRECTOR, DEPARTMENT OF TRANSPORTATION

CITY OF BALTIMORE
 DEPARTMENT OF TRANSPORTATION
 TRAFFIC DIVISION
**TRAFFIC BARRIER BOX BEAM
 MEDIAN BARRIER - DETAILS
 FOR RAISED MEDIANS**

ISSUED	REVISED	REVISED
8 / 2010		
STANDARD NO. BC 662.51-1		
SCALE: NONE	SHEET 1 OF 2	