




ANCHOR NUTS, BOLTS AND WASHERS SHALL BE HOT-DIPPED GALVANIZED IN ACCORDANCE WITH ASTM A 153. NUTS AND WASHERS SHALL MEET THE PHYSICAL AND CHEMICAL REQUIREMENTS OF ASTM A 307. BASE MOUNTED CABINET, ANCHOR NUTS, BOLTS AND WASHERS SHALL MEET THE REQUIREMENTS OF NEMA STANDARD TS-2

DIMENSION	DIMENSION SCHEDULE		
	STRAIN POLE MAST ARM POLE INNER HARBOR POLE MULTI-PURPOSE POLE	PEDESTAL POLE PUSH BUTTON POST	BASE MOUNTED CONTROL CABINET
A	60"	24"	16"
B	9"	6"	3"
C	6"	4"	2"
D	1 1/2"	1"	3/4"

* ANCHOR BOLTS FOR 32' STRAIN POLE SHALL BE 1 3/4" IN DIAMETER

	APPROVED:  DIVISION CHIEF, TRANSPORTATION ENGINEERING AND CONSTRUCTION  DIRECTOR, DEPARTMENT OF TRANSPORTATION	CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION TRANSPORTATION ENGINEERING AND CONSTRUCTION	ISSUED 8 / 2010	REVISED	REVISED
	STANDARD ANCHOR BOLTS - TRAFFIC		STANDARD NO. BC 887.02		
			SCALE : NONE	SHEET 1 OF 1	